



eW Burst Powercore gen2

BCP463 G2 19xLED-HB/4000 HMA GR

4000 K - 6° - Gray

eW Burst Powercore gen2 is a high-output, exterior-rated LED lighting luminaire designed for accent and site lighting. Architectural and Landscape versions deliver high-quality white light output in a warm 2700 K and a neutral 4000 K to support a range of uplighting, floodlighting, and decorative lighting applications.

Product data


General Information		Init. Corr. Color Temperature	
Luminaire light beam spread	6°	Init. Color Rendering Index	4000 K
CE mark	CE mark	Init. Color Rendering Index	81
UL mark	UL and cUL mark	Initial input power	30 W
FCC mark	FCC Class A	Over Time Performance (IEC Compliant)	
Operating and Electrical		Lumen Maintenance 50% at 25°C Calculated	100000
Input Voltage	100 to 277 V	Lumen Maintenance 50% at 25°C Reported	51000
Input Frequency	50 to 60 Hz	Lumen Maintenance 50% at 50°C Calculated	100000
Mechanical and Housing		Lumen Maintenance 50% at 50°C Reported	51000
Color	Gray	Lumen Maintenance 70% at 25°C Calculated	84000
Approval and Application		Lumen Maintenance 70% at 25°C Reported	51000
Ingress protection code	IP60 [Dust penetration-protected]	Lumen Maintenance 70% at 50°C Calculated	83000
Initial Performance (IEC Compliant)		Lumen Maintenance 70% at 50°C Reported	51000
Initial LED luminaire efficacy	74.6 lm/W	Lumen Maintenance 90% at 25°C Calculated	28000
		Lumen Maintenance 90% at 25°C Reported	28000
		Lumen Maintenance 90% at 50°C Calculated	27000
		Lumen Maintenance 90% at 50°C Reported	27000

eW Burst Powercore gen2

Application Conditions	
Ambient temperature range	-40 to +50 °C
Product Data	
Full product code	871869921567599
Order product name	BCP463 G2 19xLED-HB/4000 HMA GR
EAN/UPC - Product	8718699215675
Order code	912400133369

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	912400133369
Net Weight (Piece)	3.470 kg

Dimensional drawing



eW Burst Powercore gen2

