



# eW Graze MX Powercore

# BCS419 10x60/2700 L1219

2700 K - 10° x 60° - 1219 mm

Many architectural structures need a linear fixture capable of illuminating multiple storeys with minimal setback. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasize their brands. Graze MX Powercore is capable of illuminating over 20 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

## Product data

General Information	
Lamp family code	LED-HB [ LED High Brightness]
Light source colour	Warm white
Light source replaceable	No
Driver included	Yes
Luminaire light beam spread	10° x 60°
Protection class IEC	Safety class I (I)
CE mark	CE mark
UL mark	UL and cUL mark
Lifetime to 70% luminous flux	60000 h
Operating and Electrical	
Input voltage	100 to 277 V
Input frequency	50 to 60 Hz

Controls and Dimming		
Dimmable	Yes	
Mechanical and Housing		
Housing material	Aluminum extruded	
Optical cover/lens material	Polycarbonate	
Length	1219 mm	
Approval and Application		
Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK10 [ 20 J vandal-resistant]	
Vibration standard	Not compliant to ANSI C136.31, 3G. Special	
	orders are available to conform to the standard.	
	Please contact your Color Kinetics Lighting	
	Sales rep for custom configurations.	

Datasheet, 2019, October 8 data subject to change

### eW Graze MX Powercore

	Not compliant to ANSI C136.31, 3G. Special
	orders are available to conform to the standard
	Please contact your Color Kinetics Lighting
	Sales rep for custom configurations.
Initial Performance (IEC Compli	ant)
Init. Corr. colour temperature	2700 K
Initial input power	60 W
Over Time Performance (IEC Co	mpliant)
Lumen Maintenance 50% at 25°C	60000
Reported	
Lumen Maintenance 50% at 50°C	60000
Reported	
Lumen Maintenance 70% at 25°C	60000


Application Conditions	
Ambient temperature range	-20 to +50 °C
Product Data	
Full product code	871829161061800
Order product name	BCS419 10x60/2700 L1219
EAN/UPC - product	8718291610618
Order code	61061800
Numerator – quantity per pack	1
Numerator – packs per outer box	1
Material no. (12NC)	910503703736
Net weight (piece)	4.700 kg



### Dimensional drawing

Lumen Maintenance 70% at 50°C

Reported





© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, October 8 - data subject to change