



eW Flex Compact

BGC481 50 2700K CLFT4 BK

2700 K - 50 pcs - Clear flat 4 inch separated - Black

eW Flex Compact is a versatile strand of 50 individually controllable LED nodes. The flexible form factor allows dynamic points of white light to be installed across nearly any interior or exterior surface, including walls, ceilings, floors, three-dimensional sculptures, and set pieces. eW Flex Compact can also light tight alcove spaces and signage, and in certain cases, can even display video.

Product data

Datasheet, 2019, May 2

General Information	T . TA
Number of light sources	50 pcs
Lamp family code	LED-MD [LED Multi-die]
Light source replaceable	No
Driver included	No
Optical cover/lens type	Clear flat 4 inch separated
CE mark	CE mark
ENEC mark	-
UL mark	UL mark
Product recyclability	100%
RoHS mark	-
Light Technical	
Luminous intensity (peak value) on beam axis	29.8 cd
per node	
Operating and Electrical	
Input Voltage	24 V

in tignt atcov	e spaces and						
			eW Flex SLX				
N	Controls and Dimming	RAI					
	Dimmable	Yes					
ie]							
	Mechanical and Housing						
	Housing Material	Polycarbonate					
ted	Optic material	Polycarbonate					
	Color	Black					
	Approval and Application						
	Ingress protection code	IP66 [Dust penetration-protected,					
		jet-proof]					
	Mech. impact protection code	IK10 [20 J vandal-resistant]					
					PHIL	IPS	
	Initial Performance (IEC Compliant)				15		
	Init. Corr. Color Temperature	2700 K					
	Initial input power	50 W					
	Over Time Performance (IEC Compliant)						
	Lumen Maintenance 70% at 25°C Calculated	56000					
	Lumen Maintenance 70% at 25°C Reported	56000					
				1.61 16 1			

data subject to change

eW Flex Compact


Lumen Maintenance 70% at 50°C Calculated	56000
Lumen Maintenance 70% at 50°C Reported	56000
Lumen Maintenance 80% at 25°C Calculated	37000
Lumen Maintenance 80% at 25°C Reported	37000
Lumen Maintenance 80% at 50°C Calculated	37000
Lumen Maintenance 80% at 50°C Reported	37000
Lumen Maintenance 90% at 25°C Calculated	20000
Lumen Maintenance 90% at 25°C Reported	20000
Lumen Maintenance 90% at 50°C Calculated	20000
Lumen Maintenance 90% at 50°C Reported	20000

-40 to +50 °C

Product Data	
Full product code	871829164578899
Order product name	BGC481 50 2700K CLFT4 BK
EAN/UPC - Product	8718291645788
Order code	912400130620
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	912400130620
Net Weight (Piece)	0.980 kg

Dimensional drawing

Application Conditions Ambient temperature range





© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their

www.lighting.philips.com 2019, May 2 - data subject to change