



PureStyle IntelliHue Powercore

SA500X 30X60 INTELLIHUE L1220

IntelliHue - 30° x 60° - Medium beam - 1220 mm

Innovative PureStyle Powercore luminaires bring lighting professionals high output in a compact, easily concealed luminaire. PureStyle delivers exceptionally high-quality light for a wide range of interior applications – from cove to wall-washing to backlighting and beyond. Here are just some of the powerful advantages that PureStyle brings to lighting professionals and their clients.

Product data

General Information	
Light source colour	IntelliHue
Optic type	MB [Medium beam]
Optical cover/lens type	PC [Polycarbonate bowl/cover]
Luminaire light beam spread	30° x 60°
CE mark	CE mark
UL mark	UL and cUL mark
Operating and Electrical	
Input voltage	100 to 277 V
Mechanical and Housing	
Housing material	Aluminum extruded
Length	1220 mm
Colour	White

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Initial Performance (IEC Compliant)	
Initial luminous flux	2784 lm
Initial input power	52 W
Over Time Performance (IEC Compliant)	
Lumen Maintenance 50% at 25°C Calculated	72300
Lumen Maintenance 50% at 25°C Reported	47100
Lumen Maintenance 50% at 50°C Calculated	72300
Lumen Maintenance 50% at 50°C Reported	47100
Application Conditions	
Ambient temperature range	-20 to +50 °C


PureStyle IntelliHue Powercore

Product Data	
Full product code	871829139152499
Order product name	SA500X 30X60 INTELLIHUE L1220
EAN/UPC – product	8718291391524
Order code	39152499
Numerator – quantity per pack	1

Numerator – packs per outer box	6
Material no. (12NC)	912400133452
Net weight (piece)	1.847 kg



Dimensional drawing



PureStyle IntelliHue Powercore

