



Vaya Tube

BCC420 RGB FR ETH L1220 PP150 UL CE CQC

BCC420 - Ethernet

Vaya Tube is ideal for exterior accent and contour lighting applications, as well as for lowresolution graphics with a resolution of up to 150 mm (6 inches) per pixel. Up to 20 fixtures can be connected in two linear runs of 12 m (39 ft) per control module. Ethernet as well as standard DMX512 control make this product easy to use with Philips Color Kinetics or third-party DMX controllers. For more information please visit www.colorkinetics.com/vaya/.

Product data

General Information	
Lamp family code	LED-MD [LED Multi-die]
Light source color	Red, green and blue
Light source replaceable	No
Optic type	Wide beam
Optical cover/lens type	Polycarbonate bowl/cover
Luminaire light beam spread	180°
Control Interface	Ethernet
Color	Gray
CE mark	CE mark
UL mark	UL mark
CQC mark	CQC-mark
PSE mark	PSE mark
WEEE mark	WEEE mark
Product family code	BCC420

PT. M	ANTRA	WIRA SRIWIJAYA
Operating and Electrical		
Input Voltage	24 V	-
Mechanical and Housing		-
Housing Material	Polycarbonate	=
Optical cover/lens material	Polycarbonate	.
Optical cover/lens shape	Curved	•
Optical cover/lens finish	Frosted	•
Length	1220 mm	- -
Approval and Application		
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]	PHILI
Mech. Impact protection code	IK10 [20 J vandal-resistant]	49
Initial Performance (IEC Con	npliant)	
Initial luminous flux	300 lm	


Vaya Tube

-40 to +40 °C
25 °C
871829164855099
BCC420 RGB FR ETH L1220 PP150 UL CE CQC
8718291648550

Order code	912400130501
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	912400130501
Net Weight (Piece)	0.780 kg



Dimensional drawing





© 2017 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication