



C-Splash 2

BCP468 18xLED-HB/RGB 24V IP68 10 BRS

Red, green and blue - 10° - Narrow beam angle 10° - Brass

C-Splash 2 is an ultra-thin, submersible fixture designed to provide vibrant color and color-changing light in fresh and saltwater locations to a depth of 4.6 m (15 ft). With its watertight cast brass housing and silicon bronze adjusting hardware, C-Splash 2 is perfect for water-based applications such as fountains and theme park installations, as well as for applications situated in harsh environments.

Product data

General Information	
Number of light sources	18 pcs
Lamp family code	LED-HB [LED High Brightness]
Light source color	Red, green and blue
Light source replaceable	No
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Luminaire light beam spread	10°
Protection class IEC	Safety class III
CE mark	CE mark
Lifetime to 50% luminous flux	50000 h
Optic type outdoor	Narrow beam angle 10°
Operating and Electrical	
Input Voltage	24 V
Input Frequency	0 Hz
Controls and Dimming	
Dimmable	No


Mechanical and Housing	
Color	Brass
Approval and Application	
Ingress protection code	IP68 [Dust penetration-protected, pressure watertight]
Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	583 lm
Initial LED luminaire efficacy	23.3 lm/W
Initial input power	31.3 W
Over Time Performance (IEC Compliant)	
Lumen Maintenance 50% at 50°C Reported	50000
Application Conditions	
Ambient temperature range	-40 to +50 °C
Product Data	
Full product code	871794370185800

C-Splash 2

Order product name	BCP468 18xLED-HB/RGB 24V IP68 10 BRS
EAN/UPC - Product	8717943701858
Order code	910503700617
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Material Nr. (12NC)	910503700617
Net Weight (Piece)	10.000 kg

Dimensional drawing



C-Splash

