



iColor Accent Compact

BCS425 RGB FR ETH L1220 PP19

RGB - Polycarbonate bowl/cover transparent - Aluminium - 1220 mm

iColor Accent Compact is a direct view linear LED luminaire ideally suited for displaying large-scale video, graphics and intricately designed effects in a host of architectural settings. iColor Accent Compact accepts Ethernet input from the PDS-400 48V EO to support long control runs not subject to DMX data and addressing limitations. Two lens choices are available for iColor Accent Compact: a clear lens which delivers the brightest output and a translucent lens which provides the widest viewing angle.

Product data

General Information		Complies with ANSI C136.31, 3G	
Light source colour	RGB		
Optical cover/lens type	PCT [Polycarbonate bowl/cover transparent]		
Light Technical			
On-axis intensity in candela	80		
Mechanical and Housing			
Length	1220 mm		
Colour	Aluminium		
Approval and Application			
Vibration standard	Complies with ANSI C136.31, 3G		
Initial Performance (IEC Compliant)			
Initial input power	28 W		
Over Time Performance (IEC Compliant)			
Lumen Maintenance 50% at 25°C Reported	60000		
Lumen Maintenance 50% at 50°C Reported	60000		
Lumen Maintenance 70% at 25°C Reported	60000		
Lumen Maintenance 70% at 50°C Reported	60000		
Product Data			
Full product code	871829139182199		
Order product name	BCS425 RGB FR ETH L1220 PP19		

iColor Accent Compact

EAN/UPC – product	8718291391821
Order code	39182199
Numerator – quantity per pack	1
Numerator – packs per outer box	9

Material no. (12NC)	912400133773
Net weight (piece)	1.640 kg

Dimensional drawing



iColor Accent Compact

iColor Accent Compact

