



iColor Flex LMX gen2

BGC495 50 RGB CLFT12 BK

RGB - 50 pcs - Clear flat 12 inch separated - Black

iColor Flex LMX gen2 are flexible strands of large, high-intensity, full-color LED nodes designed for extraordinary effects and expansive installations without the constraints of luminaire size, shape, or space. Each iColor Flex LMX gen2 strand consists of 50 individually addressable LED nodes, featuring dynamic integration of power, communication, and control. The flexible form factor accommodates two- and three-dimensional configurations, while high light output affords superior long-distance viewing for architectural accent and perimeter lighting, large-scale signage, and building-covering video displays.

Product data

| General Information | |
|---|------------------------------|
| Number of light sources | 50 pcs |
| Lamp family code | LED-MD [LED Multi-die] |
| Light source color | RGB |
| Light source replaceable | No |
| Driver included | No |
| Optical cover/lens type | Clear flat 12 inch separated |
| Luminaire light beam spread | 105° |
| CE mark | CE mark |
| Light Technical | |
| Luminous intensity (peak value) on beam axis per node | 11 cd |
| Operating and Electrical | |
| Input Voltage | 24 V |


| Controls and Dimming | |
|-------------------------------------|---|
| Dimmable | Yes |
| Mechanical and Housing | |
| Housing Material | Polycarbonate |
| Optical cover/lens material | Polycarbonate |
| Color | Black |
| Approval and Application | |
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Initial Performance (IEC Compliant) | |
| Initial luminous flux (system flux) | 30 lm |
| Initial LED luminaire efficacy | 30 lm/W |
| Initial input power | 1W |

iColor Flex LMX gen2

| Over Time Performance (IEC Compliant) | |
|--|---------------|
| Useful life L80B10 | 60000 h |
| Lumen Maintenance 50% at 25°C Calculated | 100000 |
| Lumen Maintenance 50% at 25°C Reported | 60000 |
| Lumen Maintenance 50% at 50°C Calculated | 100000 |
| Lumen Maintenance 50% at 50°C Reported | 60000 |
| Lumen Maintenance 70% at 25°C Calculated | 100000 |
| Lumen Maintenance 70% at 25°C Reported | 60000 |
| Lumen Maintenance 70% at 50°C Calculated | 100000 |
| Lumen Maintenance 70% at 50°C Reported | 60000 |
| Application Conditions | |
| Ambient temperature range | -40 to +50 °C |

| Product Data | |
|---------------------------------|-------------------------|
| Full product code | 871829162307699 |
| Order product name | BGC495 50 RGB CLFT12 BK |
| EAN/UPC - Product | 8718291623076 |
| Order code | 912400130023 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 6 |
| Material Nr. (12NC) | 912400130023 |
| Net Weight (Piece) | 0.980 kg |

Dimensional drawing



iColor Flex LMX gen2

