



eW Reach Compact Powercore

DCP400 4000 CO 100-277V UL CE

4000 K - 5° - 100 to 277 V - Flat glass - Aluminum

eW Reach Compact Powercore high-performance LED luminaires are premium exterior long-throw dynamic high-quality white luminaires for lighting tall buildings, bridges, and iconic structures. eW Reach Compact Powercore outputs washes of white light in color temperatures ranging from a warm 2700 K to a cool 6500 K. A full range of accessories allow for customizable beam angles for floodlighting, spotlighting, wall washing, and grazing, along with the efficiency and cost-effectiveness of Powercore technology in a rugged die-cast aluminium housing.

Product data

General Information	
Number of light sources	52 pcs
Lamp family code	LED-HB [LED High Brightness]
Light source color	Cool white
Light source replaceable	No
Driver/power unit/transformer	Power supply unit regulating
Driver included	Yes
Optical cover/lens type	Flat glass
Luminaire light beam spread	5°
Protection class IEC	Safety class I
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
UL mark	UL and cUL mark
Warranty period	5 years

FCC mark	FCC Class A
RoHS mark	RoHS mark
WEEE mark	WEEE mark

Operating and Electrical

Input Voltage	100 to 277 V
Input Frequency	50 to 60 Hz
Power Factor (Nom)	0.99 (no spread lens, full unit, all channels full on) @ 120 VAC

Mechanical and Housing

Housing Material	Aluminum die cast
Optic material	Glass
Optical cover/lens material	Tempered glass
Optical cover/lens finish	Clear

eW Reach Compact Powercore

Color	Aluminum
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	7441 lm
Initial luminous flux at color temperature of 4000 K	7441 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	59.8 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	82
Initial input power	125 W
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compliant)	
Useful life L80B10	100000 h
Lumen Maintenance 70% at 25°C Calculated	100000

Lumen Maintenance 70% at 50°C Calculated	100000
Lumen Maintenance 80% at 25°C Calculated	100000
Lumen Maintenance 80% at 50°C Calculated	100000
Lumen Maintenance 90% at 25°C Reported	42300
Lumen Maintenance 90% at 50°C Reported	42300

Application Conditions

Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Product Data

Full product code	871829139017600
Order product name	DCP400 4000 CO 100-277V UL CE
EAN/UPC - Product	8718291390176
Order code	912400133475
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912400133475
Net Weight (Piece)	23.400 kg

Dimensional drawing

Reach Compact

