PHILIPS Lighting




PureStyle IntelliHue Powercore

| Product Data | |
|-------------------------------|-------------------------------|
| Full product code | 871829139153199 |
| Order product name | SA500X 10X60 INTELLIHUE L1220 |
| EAN/UPC - Product | 8718291391531 |
| Order code | 912400133453 |
| Numerator - Quantity Per Pack | 1 |

| Numerator - Packs per outer box | 6 | |
|---------------------------------|--------------|--|
| Material Nr. (12NC) | 912400133453 | |
| Net Weight (Piece) | 1.847 kg | |

Dimensional drawing



PureStyle IntelliHue Powercore

SA500X 10X60 INTELLIHUE L1220

IntelliHue - 10° x 60° - Narrow beam - 1220 mm

Innovative PureStyle Powercore luminaires bring lighting professionals high output in a compact, easily concealed luminaire. PureStyle delivers exceptionally highquality light for a wide range of interior applications - from cove to wall-washing to NTRA WIRA SRIWIJAYA backlighting and beyond. Here are just some of the powerful advantages that PureStyle brings to lighting professionals and their clients.

Product data

| General Information | | Ар |
|-----------------------------|--------------------------|------|
| Light source color | IntelliHue | Ing |
| Optic type | Narrow beam | |
| Optical cover/lens type | Polycarbonate bowl/cover | Ini |
| Luminaire light beam spread | 10° x 60° | Init |
| CE mark | CE mark | Init |
| UL mark | UL and cUL mark | |
| | | Ov |
| Operating and Electrical | | Lur |
| Input Voltage | 100 to 277 V | Lur |
| | | Lur |
| Mechanical and Housing | | Lur |
| Housing Material | Aluminum extruded | |
| Length | 1220 mm | Ар |
| Color | White | Am |

| Approval and Application | |
|--|--------------------------|
| Ingress protection code | IP20 [Finger-protected] |
| | |
| Initial Performance (IEC Compliant) | |
| Initial luminous flux (system flux) | 3056 lm |
| Initial input power | 52 W |
| | |
| Over Time Performance (IEC Compliant) | |
| Lumen Maintenance 50% at 25°C Calculated | 72300 |
| Lumen Maintenance 50% at 25°C Reported | 47100 |
| Lumen Maintenance 50% at 50°C Calculated | 72300 |
| Lumen Maintenance 50% at 50°C Reported | 47100 |
| | |
| Application Conditions | |
| Ambient temperature range | -20 to +50 °C |
| | |



IP 20

© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, September 20 - data subject to change

data subject to change