



iColor Accent Compact

BCS425 RGB CL ETH L305 PP19

RGB - Polycarbonate bowl/cover UV-resistant - Aluminum - 305 mm

iColor Accent Compact is a direct view linear LED luminaire ideally suited for displaying large-scale video, graphics, and intricately designed effects in a host of architectural settings. iColor Accent Compact accepts Ethernet input from the PDS-400 48V EO to support long control runs not subject to DMX data and addressing limitations. Two lens choices are available for iColor Accent Compact: a clear lens which delivers the brightest output and a translucent lens which provides the widest viewing angle.

Product data

General Information	
Light source color	RGB
Optical cover/lens type	Polycarbonate bowl/cover UV-resistant
Luminaire light beam spread	105°
Light Technical	
On-axis intensity in candela	47
Mechanical and Housing	
Length	305 mm
Color	Aluminum
Approval and Application	
Vibration Standard	Complies with ANSI C136.31, 3G



Vibration Rating	Complies with ANSI C136.31, 3G
Initial Performance (IEC Compliant)	
Initial input power	10 W
Over Time Performance (IEC Compliant)	
Lumen Maintenance 50% at 25°C Reported	60000
Lumen Maintenance 50% at 50°C Reported	60000
Lumen Maintenance 70% at 25°C Reported	60000
Lumen Maintenance 70% at 50°C Reported	60000
Product Data	
Full product code	871829139183899
Order product name	BCS425 RGB CL ETH L305 PP19

iColor Accent Compact

EAN/UPC - Product	8718291391838
Order code	912400133774
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	9

Material Nr. (12NC)	912400133774
Net Weight (Piece)	0.610 kg

Dimensional drawing



iColor Accent Compact

iColor Accent Compact

