



ColorGraze QLX Powercore

BCS467 10x60 RGB L609

RGB - 10° x 60° - 609 mm - aluminum

ColorGraze QLX Powercore is a high-performance, exterior linear luminaire designed to highlight architectural features ranging from surface textures and molding details to archways and windows. Graze RGB luminaires offer rich, saturated color and color-changing effects. Multiple fixture lengths, beam angles, output levels, and power consumption levels support a large range of façade or surface illumination application. Low-profile housing, connectorized cabling, a universal power input range, and direct line voltage operation make Graze luminaires easy to install and operate.

Product data

Lamp family code Light source color	LED-HB [LED High Brightness]
Light source color	RGB
Light source replaceable	No
Driver included	Yes
Luminaire light beam spread	10° x 60°
Protection class IEC	Safety class I
CE mark	CE mark
UL mark	UL and cUL mark
Lifetime to 70% luminous flux	100000 h
Operating and Electrical	
Input Voltage	100 to 277 V


Input Frequency	50 to 60 Hz	
		_
Controls and Dimming		
Dimmable	Yes	
Mechanical and Housing		
Housing Material	Aluminum extruded	
Optic material	Polycarbonate	
Optical cover/lens material	Polycarbonate	
Length	609 mm	
Color	aluminum	

ColorGraze QLX Powercore

Approval and Application		
Ingress protection code	IP66 [Dust penetration-protected, jet-	
	proof]	
Mech. impact protection code	IK10 [20 J vandal-resistant]	
Vibration Standard	Complies with ANSI C136.31, 3G	
Vibration Rating	Complies with ANSI C136.31, 3G	
Initial Performance (IEC Compliant)		
Initial input power	30 W	
Over Time Performance (IEC Compliant)		
Lumen Maintenance 50% at 25°C Calculated	100000	
Lumen Maintenance 50% at 25°C Reported	100000	
Lumen Maintenance 50% at 50°C Calculated 80000		
Lumen Maintenance 50% at 50°C Reported	80000	
Lumen Maintenance 70% at 25°C Calculated	60000	
Lumen Maintenance 70% at 25°C Reported	100000	
Lumen Maintenance 70% at 50°C Calculated	60000	

Lumen Maintenance 70% at 50°C Reported	91000
Application Conditions	
Ambient temperature range	-40 to +50 °C
Product Data	·
Full product code	871829160409999
Order product name	BCS467 10x60 RGB L609
EAN/UPC - Product	8718291604099
Order code	910503703353
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	910503703353
Net Weight (Piece)	2.700 kg

Dimensional drawing





© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their

Datasheet, 2019, May 1 data subject to change information presented in this document is not intended as any common data subject.

www.lighting.philips.com 2019, May 1 - data subject to change