



ColorReach Compact Powercore

DCP403 RGB CO 100-277V UL CE

RGB - 5° - 100 to 277 V - Aluminum

ColorReach Compact Powercore high-performance LED luminaires are premium exterior long-throw dynamic color-changing luminaires for lighting tall buildings, bridges, and iconic structures. With ColorReach Compact Powercore, RGB you get intensely saturated RGB light. ColorReach Compact Powercore offers a range of accessories that allow for customizable beam angles for floodlighting, spotlighting, wall washing, and grazing, along with the efficiency and cost-effectiveness of Powercore technology in a rugged die-cast aluminium housing.

Product data

General Information	
Number of light sources	52 pcs
Lamp family code	LED-HB [LED High Brightness]
Light source color	RGB
Light source replaceable	No
Driver/power unit/transformer	Power supply unit regulating
Driver included	Yes
Optical cover/lens type	Flat glass
Luminaire light beam spread	5°
Protection class IEC	Safety class I
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
UL mark	UL and cUL mark
Warranty period	5 years

FCC mark	FCC Class A
RoHS mark	RoHS mark
WEEE mark	WEEE mark
Life to 70% init flux at 25 °C	100000 h
Operating and Electrical	
Input Voltage	100 to 277 V
Input Frequency	50 to 60 Hz
Control signal voltage	1-10 V DC
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing Material	Aluminum die cast

ColorReach Compact Powercore

Optic material	Glass
Optical cover/lens material	Tempered glass
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Color	Aluminum

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]

Initial Performance (IEC Compliant)

Initial Luminous flux (system flux)	4658 lm
Init. Color Rendering Index	82
Initial input power	130 W
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Lumen Maintenance 70% at 25°C Calculated	100000
--	--------

Lumen Maintenance 70% at 50°C Calculated	100000
--	--------

Application Conditions

Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Product Data

Full product code	871829139012100
Order product name	DCP403 RGB CO 100-277V UL CE
EAN/UPC - Product	8718291390121
Order code	912400133610
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912400133610
Net Weight (Piece)	23.400 kg

Dimensional drawing

Reach Compact

