



# PureStyle IntelliHue Powercore

## SA500X 30X60 INTELLIHUE L305

IntelliHue - 30° x 60° - Medium beam - 305 mm

Innovative PureStyle Powercore luminaires bring lighting professionals high output in a compact, easily concealed luminaire. PureStyle delivers exceptionally high-quality light for a wide range of interior applications – from cove to wall-washing to backlighting and beyond. Here are just some of the powerful advantages that PureStyle brings to lighting professionals and their clients.

### Product data

General Information	
Light source colour	IntelliHue
Optic type	MB [ Medium beam]
Optical cover/lens type	PC [ Polycarbonate bowl/cover]
Luminaire light beam spread	30° x 60°
CE mark	CE mark
UL mark	UL and cUL mark
Operating and Electrical	
Input voltage	100 to 277 V
Mechanical and Housing	
Housing material	Aluminum extruded
Length	305 mm
Colour	White

Approval and Application	
Ingress protection code	IP20 [ Finger-protected]
Initial Performance (IEC Compliant)	
Initial luminous flux	696 lm
Initial input power	13 W
Over Time Performance (IEC Compliant)	
Lumen Maintenance 50% at 25°C Calculated	72300
Lumen Maintenance 50% at 25°C Reported	47100
Lumen Maintenance 50% at 50°C Calculated	72300
Lumen Maintenance 50% at 50°C Reported	47100
Application Conditions	
Ambient temperature range	-20 to +50 °C


### PureStyle IntelliHue Powercore

Product Data	
Full product code	871829139149499
Order product name	SA500X 30X60 INTELLIHUE L305
EAN/UPC – product	8718291391494
Order code	39149499
Numerator – quantity per pack	1

Numerator – packs per outer box	20
Material no. (12NC)	912400133449
Net weight (piece)	0.485 kg



### Dimensional drawing



PureStyle IntelliHue Powercore

