



# ColorGraze QLX Powercore

## BCS467 15x30 RGB L609

RGB - 15° x 30° - 609 mm - aluminum

ColorGraze QLX Powercore is a high-performance, exterior linear luminaire designed to highlight architectural features ranging from surface textures and molding details to archways and windows. Graze RGB luminaires offer rich, saturated color and color-changing effects. Multiple fixture lengths, beam angles, output levels, and power consumption levels support a large range of façade or surface illumination application. Low-profile housing, connectorized cabling, a universal power input range, and direct line voltage operation make Graze luminaires easy to install and operate.

### Product data

General Information	
Lamp family code	LED-HB [ LED High Brightness]
Light source color	RGB
Light source replaceable	No
Driver included	Yes
Luminaire light beam spread	15° x 30°
Protection class IEC	Safety class I
CE mark	CE mark
UL mark	UL and cUL mark
Lifetime to 70% luminous flux	100000 h
Operating and Electrical	
Input Voltage	100 to 277 V


Input Frequency	50 to 60 Hz	
Controls and Dimming		
Dimmable	Yes	
Mechanical and Housing		
Housing Material	Aluminum extruded	
Optic material	Polycarbonate	
Optical cover/lens material	Polycarbonate	
Length	609 mm	
Color	aluminum	

# ColorGraze QLX Powercore

Approval and Application	
Ingress protection code	IP66 [ Dust penetration-protected, jet-
	proof]
Mech. impact protection code	IK10 [ 20 J vandal-resistant]
Vibration Standard	Complies with ANSI C136.31, 3G
Vibration Rating	Complies with ANSI C136.31, 3G
Initial Performance (IEC Compliant)	
Initial input power	30 W
Over Time Performance (IEC Complian	t)
Lumen Maintenance 50% at 25°C Calculated	100000
Lumen Maintenance 50% at 25°C Reported	100000
Lumen Maintenance 50% at 50°C Calculated	80000
Lumen Maintenance 50% at 50°C Reported	80000
Lumen Mainten <mark>ance 7</mark> 0% at 25°C Calculated	60000
Lumen Maintenance 70% at 25°C Reported	100000
Lumen Maintenance 70% at 50°C Calculated	60000

Lumen Maintenance 70% at 50°C Reported	91000
Application Conditions	
Ambient temperature range	-40 to +50 °C
Product Data	
Full product code	871829160410599
Order product name	BCS467 15x30 RGB L609
EAN/UPC - Product	8718291604105
Order code	910503703354
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	910503703354
Net Weight (Piece)	2.700 kg

# Dimensional drawing





© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their

Datasheet, 2019, May 1 data subject to change information presented in this document is not intended as any commercial offer and does not form

www.lighting.philips.com 2019, May 1 - data subject to change