



# PureStyle IntelliHue Powercore

## SA500X 10X60 INTELLIHUE L305

IntelliHue - 10° x 60° - Narrow beam - 305 mm

Innovative PureStyle Powercore luminaires bring lighting professionals high output in a compact, easily concealed luminaire. PureStyle delivers exceptionally high-quality light for a wide range of interior applications – from cove to wall-washing to backlighting and beyond. Here are just some of the powerful advantages that PureStyle brings to lighting professionals and their clients.

### Product data

General Information	
Light source color	IntelliHue
Optic type	Narrow beam
Optical cover/lens type	Polycarbonate bowl/cover
Luminaire light beam spread	10° x 60°
CE mark	CE mark
UL mark	UL and cUL mark
Operating and Electrical	
Input Voltage	100 to 277 V
Mechanical and Housing	
Housing Material	Aluminum extruded
Length	305 mm
Color	White

Approval and Application	
Ingress protection code	IP20 [ Finger-protected]
Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	764 lm
Initial input power	13 W
Over Time Performance (IEC Compliant)	
Lumen Maintenance 50% at 25°C Calculated	72300
Lumen Maintenance 50% at 25°C Reported	47100
Lumen Maintenance 50% at 50°C Calculated	72300
Lumen Maintenance 50% at 50°C Reported	47100
Application Conditions	
Ambient temperature range	-20 to +50 °C


### PureStyle IntelliHue Powercore

Product Data	
Full product code	871829139150099
Order product name	SA500X 10X60 INTELLIHUE L305
EAN/UPC - Product	8718291391500
Order code	912400133450
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	20
Material Nr. (12NC)	912400133450
Net Weight (Piece)	0.485 kg



### Dimensional drawing



PureStyle IntelliHue Powercore

