



eW Cove EC Powercore

BCX422 2700 HE L152 CE/CCC

LED High Brightness - Power supply unit - Polycarbonate bowl/cover - 110° x 110°

eW Cove EC Powercore is a dimmable, linear LED luminaire that provides an affordable, energy-efficient alternative to traditional cove lighting in applications requiring white light. With its low profile, rotating housing and flexible end-to-end locking power connectors, eW Cove EC Powercore is the perfect choice for a wide range of interior retail, exhibit, hospitality, and architectural settings.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Light source color	Warm white
Lamp system description	High efficiency
Light source replaceable	No
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optical cover/lens type	Polycarbonate bowl/cover
Luminaire light beam spread	110° x 110°
Protection class IEC	Safety class II
Glow-wire test	Temperature 650 °C, duration 5 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
ENEC mark	-
UL mark	UL mark

CCC mark	CCC mark
Operating and Electrical	
Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing Material	Plastic
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Length	152 mm
Color	Dark gray

eW Cove EC Powercore

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	111 lm
Initial luminous flux at color temperature of 2700 K	111 lm
Initial LED luminaire efficacy	64 lm/W
Init. Corr. Color Temperature	2700 K
Init. Color Rendering Index	83
Initial input power	2.3 W
Over Time Performance (IEC Compliant)	
Lumen Maintenance 70% at 25°C Calculated	100000
Lumen Maintenance 70% at 25°C Reported	37000
Lumen Maintenance 70% at 50°C Calculated	100000
Lumen Maintenance 70% at 50°C Reported	37000
Lumen Maintenance 80% at 25°C Calculated	100000
Lumen Maintenance 80% at 25°C Reported	37000
Lumen Maintenance 80% at 50°C Calculated	100000
Lumen Maintenance 80% at 50°C Reported	37000


Lumen Maintenance 90% at 25°C Calculated	47000
Lumen Maintenance 90% at 25°C Reported	37000
Lumen Maintenance 90% at 50°C Calculated	47000
Lumen Maintenance 90% at 50°C Reported	37000

Application Conditions	
Ambient temperature range	-20 to +50 °C

Product Data	
Full product code	871829164049399
Order product name	BCX422 2700 HE L152 CE/CCC
EAN/UPC - Product	8718291640493
Order code	912400133248
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	912400133248
Net Weight (Piece)	0.103 kg



Dimensional drawing



eW Cove EC Powercore



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.