



eW Flex Compact

BGC481 50 4000K CLFT4 BK

4000 K - 50 pcs - Clear flat 4 inch separated - Black

eW Flex Compact is a versatile strand of 50 individually controllable LED nodes. The flexible form factor allows dynamic points of white light to be installed across nearly any interior or exterior surface, including walls, ceilings, floors, three-dimensional sculptures, and set pieces. eW Flex Compact can also light tight alcove spaces and signage, and in certain cases, can even display video.

Product data

General Information	
Number of light sources	50 pcs
Lamp family code	LED-MD [LED Multi-die]
Light source replaceable	No
Driver included	No
Optical cover/lens type	Clear flat 4 inch separated
CE mark	CE mark
ENEC mark	-
UL mark	UL mark
Product recyclability	100%
RoHS mark	-
Light Technical	
Luminous intensity (peak value) on beam axis per node	31.5 cd
Operating and Electrical	
Input Voltage	24 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing Material	Polycarbonate
Optic material	Polycarbonate
Color	Black
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Initial Performance (IEC Compliant)	
Init. Corr. Color Temperature	4000 K
Initial input power	1 W
Over Time Performance (IEC Compliant)	
Lumen Maintenance 70% at 25°C Calculated	56000
Lumen Maintenance 70% at 25°C Reported	56000

eW Flex Compact


Lumen Maintenance 70% at 50°C Calculated	56000
Lumen Maintenance 70% at 50°C Reported	56000
Lumen Maintenance 80% at 25°C Calculated	37000
Lumen Maintenance 80% at 25°C Reported	37000
Lumen Maintenance 80% at 50°C Calculated	37000
Lumen Maintenance 80% at 50°C Reported	37000
Lumen Maintenance 90% at 25°C Calculated	20000
Lumen Maintenance 90% at 25°C Reported	20000
Lumen Maintenance 90% at 50°C Calculated	20000
Lumen Maintenance 90% at 50°C Reported	20000

Product Data	
Full product code	871829164602099
Order product name	BGC481 50 4000K CLFT4 BK
EAN/UPC - Product	8718291646020
Order code	912400130644
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	912400130644
Net Weight (Piece)	0.980 kg

Application Conditions

Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Dimensional drawing



eW Flex SLX

